



1	VSS	Power ground
2	VDD	Power supply (+5V)
3	V0	Contrast adjust
4	/WR	Write signal
5	/RD	Read signal
6	/CE	Chip select
7	C/D	H: Command; L:Data
8	/RST	Reset signal
9	DB0	DATA BUS 0
10	DB1	DATA BUS 1
11	DB2	DATA BUS 2
12	DB3	DATA BUS 3
13	DB4	DATA BUS 4
14	DB5	DATA BUS 5
15	DB6	DATA BUS 6
16	DB7	DATA BUS 7
17	FS	Font type. L:8X8; H:6X8
18	VEE	Internal negative voltage output.
19	K	Backlight (-)
20	A	Backlight (+) +5V

NOTES:

1. DISPLAY TYPE: STN,BLUE
2. POLARIZER TYPE: TRANSMISSIVE,NEGATIVE
3. VIEW DIRECTION: 6:00
4. OPERATING TEMPERATURE: -20°C~+70°C
5. STORAGE TEMPERATURE: -30°C~+80°C
6. VDD: +5V
7. DRIVE METHOD: 1/128DUTY,1/12BIAS
8. CONTROLLER: T6963C
9. BACKLIGHT TYPE: YELLOW-GREEN,BOTTOM
10. BACKLIGHT SUPPLY VOLTAGE: +5.0V
11. VOP: TBD

WAYING WAYING (HONGKONG) SHARES LIMITED

DESIGN:	MODEL NUMBER:	UNITS:	MM
CHECK:	WYM128128A2	VERSION:	A
APPROVE:		SHEET:	1 OF 1
Unspecified tolerances are ±0.3		DATE:	2006-03-01