



1	VSS	Power ground
2	VDD	Power supply (+3.3V)
3	NC	/
4	DB7	DATA BUS 7 (serial: SI)
5	DB6	DATA BUS 6 (serial: SCL)
6	DB5	DATA BUS 5
7	DB4	DATA BUS 4
8	DB3	DATA BUS 3
9	DB2	DATA BUS 2
10	DB1	DATA BUS 1
11	DB0	DATA BUS 0
12	E	Enable signal
13	R/W	H: Read; L: Write
14	RS	Register select. H:DATA; L:INSTRUCTION
15	RST	Reset select
16	/CS	Chip select
17	NC	/
18	NC	/
19	A	Backlight (+) +3.3V
20	K	Backlight (-)

- NOTES:
1. DISPLAY TYPE: STN
  2. POLARIZER TYPE: TRANSPARENT, POSITIVE
  3. VIEW DIRECTION: 6:00
  4. OPERATING TEMPERATURE: -20°C~+70°C
  5. STORAGE TEMPERATURE: -30°C~+80°C
  6. VDD: +3.3V
  7. DRIVE METHOD: 1/32DUTY, 1/7BIAS
  8. CONTROLLER: SPLC502B
  9. BACKLIGHT TYPE: WHITE, SIDE
  10. BACKLIGHT SUPPLY VOLTAGE: +3.3V
  11. VOP: TBD

		DESIGN:	MODEL NUMBER:	UNITS:	MM
		CHECK:	WYM12832K4	VERSION:	A
APPROVE:			SHEET:	1 OF 1	
Unspecified tolerances are ±0.3					
DATE: 2012-02-14					