


1	NC	
2	VSS	Power ground
3	VDD	Power supply (+3.3V)
4	DB7(scl)	DATA BUS 7(serial data)
5	DB6(scl)	DATA BUS 6(serial clock)
6	DB5	DATA BUS 5
7	DB4	DATA BUS 4
8	DB3	DATA BUS 3
9	DB2	DATA BUS 2
10	DB1	DATA BUS 1
11	DB0	DATA BUS 0
12	E	Enable signal
13	R/W	Read/Write signal
14	A0	H:data; L: instruction
15	/RES	Reset signal
16	/CS1	Chip select
17	A	Backlight (+) +3.3V
18	K	Backlight (-)

NOTES:

1. DISPLAY TYPE: STN,YELLOW-GREEN
2. POLARIZER TYPE: TRANSPARENT, POSITIVE
3. VIEW DIRECTION: 6:00
4. OPERATING TEMPERATURE: -10°C~+60°C
5. STORAGE TEMPERATURE: -20°C~+70°C
6. VDD: +3.3V
7. DRIVE METHOD: 1/64DUTY, 1/9BIAS
8. CONTROLLER: ST7565P
9. BACKLIGHT TYPE: WHITE
10. BACKLIGHT SUPPLY VOLTAGE: +3.3V

 WAYING (HONGKONG) SHARES LIMITED	
DESIGN:	MODEL NUMBER:
CHECK:	WYM12864K11
APPROVE:	UNITS: MM
Unspecified tolerances are ±0.3	VERSION: A
	SHEET: 1 OF 1
	DATE: 2012-03-05