



1	NC	
2	NC	
3	NC	
4	NC	
5	A	Backlight (+) +3.3V
6	VSS	Power ground
7	VDD	Power supply (+3.3V)
8	DB6(sct)	DATA BUS 6(serial clock)
9	DB7(sct)	DATA BUS 7(serial data)
10	A0	H:data; L: instruction
11	/RES	Reset signal
12	/CS1	Chip select

NOTES:

1. DISPLAY TYPE: FSTN
2. POLARIZER TYPE: TRANSPARENT, POSITIVE
3. VIEW DIRECTION: 6:00
4. OPERATING TEMPERATURE: -20°C~+70°C
5. STORAGE TEMPERATURE: -30°C~+80°C
6. VDD: +3.3V
7. DRIVE METHOD: 1/64DUTY, 1/9BIAS
8. CONTROLLER: UC1701
9. BACKLIGHT TYPE: WHITE
10. BACKLIGHT SUPPLY VOLTAGE: +3.3V

WAYING (HONGKONG) SHARES LIMITED

DESIGN:

MODEL NUMBER:

UNITS: MM

CHECK:

WYM12864K6

VERSION: A

APPROVE:

SHEET: 1 OF 1

Unspecified tolerances are ±0.3

DATE: 2014-09-17