



1	/CS1	Chip select
2	/RES	Reset signal
3	A0	"H": Data ; "L": Instruction
4	R/W	"H": Read ; "L": Write
5	E	Enable signal
6	DB0	DATA BUS 0
7	DB1	DATA BUS 1
8	DB2	DATA BUS 2
9	DB3	DATA BUS 3
10	DB4	DATA BUS 4
11	DB5	DATA BUS 5
12	DB6(sc1)	DATA BUS 6
13	DB7(sc1)	DATA BUS 7
14	VSS	Power ground
15	VDD	Power supply (+3.3V)
16	A	Backlight (+) +3.3V
17	K	Backlight (-)

NOTES:

1. DISPLAY TYPE: STN,BLUE
2. POLARIZER TYPE: TRANSMISSIVE,NEGATIVE
3. VIEW DIRECTION: 6:00
4. OPERATING TEMPERATURE: -20°C~+70°C
5. STORAGE TEMPERATURE: -30°C~+80°C
6. VDD: +3.3V
7. DRIVE METHOD: 1/64DUTY,1/9BIAS
8. CONTROLLER: ST7565P
9. BACKLIGHT TYPE: WHITE,SIDE
10. BACKLIGHT SUPPLY VOLTAGE: +3.3V
11. VOP: TBD

WAYING (HONGKONG) SHARES LIMITED	
DESIGN:	MODEL NUMBER:
CHECK:	WYM12864K8
APPROVE:	UNITS: MM
	VERSION: B
	SHEET: 1 OF 1
Unspecified tolerances are ±0.3	
DATE: 2011-03-22	