


1	VSS	Power ground
2	VDD	Power supply (+5V)
3	V0	Contrast adjust
4	RS	Register select
5	R/W	H: Read, L: Write
6	E	Enable signal
7	DB0	DATA BUS 0
8	DB1	DATA BUS 1
9	DB2	DATA BUS 2
10	DB3	DATA BUS 3
11	DB4	DATA BUS 4
12	DB5	DATA BUS 5
13	DB6	DATA BUS 6
14	DB7	DATA BUS 7
15	A	Backlight (+) +5V
16	K	Backlight (-)

- NOTES:
1. DISPLAY TYPE: STN, YELLOW-GREEN
  2. POLARIZER TYPE: TRANSPARENT, POSITIVE
  3. VIEW DIRECTION: 6:00
  4. OPERATING TEMPERATURE: -20°C~+70°C
  5. STORAGE TEMPERATURE: -30°C~+80°C
  6. VDD: +5V
  7. DRIVE METHOD: 1/16DUTY, 1/5BIAS
  8. CONTROLLER: S6A0069
  9. BACKLIGHT TYPE: YELLOW-GREEN, BOTTOM
  10. BACKLIGHT SUPPLY VOLTAGE: +5.0V
  11. VOP: TBD



		DESIGN:	MODEL NUMBER:	UNITS:	MM
		CHECK:	WYM1602A	VERSION:	A
APPROVE:			SHEET:	1 OF 1	
Unspecified tolerances are ±0.3					
DATE: 2006-08-08					