



1	FG	Frame ground
2	VSS	Power ground
3	VDD	Power supply (+5V)
4	VO	Contrast adjust
5	/WR	Data write
6	/RD	Data read
7	/CE	Chip Enable for T6963C
8	C/D	H: Command; L:Data
9	/RST	Reset signal
10-17	D0-D7	DATA BUS
18	FS	Font type. L:8X8; H:6X8
19	A	Backlight (+) +5V
20	K	Backlight (-)
21	VOVT	Negative power output

NOTES:

1. DISPLAY TYPE: STN,BLUE
2. POLARIZER TYPE: TRANSMISSIVE,NEGATIVE
3. VIEW DIRECTION: 6:00
4. OPERATING TEMPERATURE: -20°C~+70°C
5. STORAGE TEMPERATURE: -30°C~+80°C
6. VDD: +5V
7. DRIVE METHOD: 1/128DUTY,1/12BIAS
8. CONTROLLER: T6963C
9. BACKLIGHT TYPE: WHITE
10. BACKLIGHT SUPPLY VOLTAGE: +5.0V

<p>WAYING WAYING (HONGKONG) SHARES LIMITED</p>		DESIGN:	MODEL NUMBER:	UNITS:	MM
		CHECK:	WYM240128A5	VERSION:	A
APPROVE:			SHEET:	1 OF 1	
Unspecified tolerances are ±0.3			DATE:	2011-01-07	