



1	SEL1	8090(L) or 6900(H) family interface select.
2	/RST	Reset signal
3	/RD	Data read
4	/WR	Data write
5	A0	H: Command; L:Data
6	/CS	Chip select for SED1335.
7	D0	DATA BUS 0
8	D1	DATA BUS 1
9	D2	DATA BUS 2
10	D3	DATA BUS 3
11	D4	DATA BUS 4
12	D5	DATA BUS 5
13	D6	DATA BUS 6
14	D7	DATA BUS 7
15	VDD	Power supply (+5V)
16	VO	Contrast adjust
17	VEE	+25V output
18	VSS	Power ground
19	K	Backlight power (-)
20	A	Backlight power (+5V)
21	E-LED	LED enable

NOTES:

1. DISPLAY TYPE: FSTN
2. POLARIZER TYPE: TRANSPARENT, POSITIVE
3. VIEW DIRECTION: 6:00
4. OPERATING TEMPERATURE: -20°C~+70°C
5. STORAGE TEMPERATURE: -30°C~+80°C
6. VDD: +5V
7. DRIVE METHOD: 1/240DUTY, 1/13BIAS
8. CONTROLLER: RA8835 OR EQUIVALENT
9. BACKLIGHT TYPE: WHITE,LED
10. BACKLIGHT SUPPLY VOLTAGE: +5.0V
11. VOP: TBD

WAYING (HONGKONG) SHARES LIMITED		DESIGN:	MODEL NUMBER:	UNITS:	MM
		CHECK:	WYM320240C2	VERSION:	A
APPROVE:			SHEET:	1 OF 1	
Unspecified tolerances are ±0.3			DATE:	2008-09-12	