



1	VSS	Power ground
2	VDD	Power supply (+5V)
3	VO	Contrast adjust
4	/WR	Data write
5	/RD	Data read
6	/CS	Chip select for SED1335.
7	RS	H: Command; L:Data
8	/RST	Reset signal
9	D0	DATA BUS 0
10	D1	DATA BUS 1
11	D2	DATA BUS 2
12	D3	DATA BUS 3
13	D4	DATA BUS 4
14	D5	DATA BUS 5
15	D6	DATA BUS 6
16	D7	DATA BUS 7
17	BUSY	Busy check
18	VEE	Negative power output
19	A	Backlight power (+5V)
20	K	Backlight power (-)

NOTES:

1. DISPLAY TYPE: FSTN
2. POLARIZER TYPE: TRANSPARENT, POSITIVE
3. VIEW DIRECTION: 6:00
4. OPERATING TEMPERATURE: -20°C~+70°C
5. STORAGE TEMPERATURE: -30°C~+80°C
6. VDD: +5V
7. DRIVE METHOD: 1/240DUTY, 1/13BIAS
8. CONTROLLER: RA8806
9. BACKLIGHT TYPE: WHITE,LED
10. BACKLIGHT SUPPLY VOLTAGE: +5.0V
11. VOP: TBD

		DESIGN:	MODEL NUMBER:	UNITS:	MM
		CHECK:	WYM320240C3	VERSION:	A
APPROVE:				SHEET:	1 OF 1
Unspecified tolerances are ±0.3				DATE:	2009-07-16