



Pin	Symbol	Connection
30	PS0	+3.0V
29	PS1	
28	CSB	P3.0
27	RST	P3.1
26	A0	P3.2
25	EWIR	P3.3
24	ERD	P3.4
23	D0	P1.0
22	D1	P1.1
21	D2	P1.2
20	D3	P1.3
19	D4	P1.4
18	D5	P1.5
17	D6(SCL)	P1.6
16	D7(SI)	P1.7
15	VDD	+3.0V
14	VSS	
13	VMD	
12	NC	x
11	V0	
10	XV0	
9	VDD1	+3.0V
8	OSCT	
7	DCPS	
6	VSS1	
5	CSEL	
4	V01	+3.0V
3	VG	
2	VPP	x
1	VE	x



SCALE: 10:1



CON8SFG LAYOUT

- NOTES:
1. DISPLAY TYPE: FSTN
  2. POLARIZER TYPE: TRANSPARENT, POSITIVE
  3. VIEW DIRECTION: 6:00
  4. OPERATING TEMPERATURE: -20°C~+70°C
  5. STORAGE TEMPERATURE: -30°C~+80°C
  6. VDD: +3.3V
  7. DRIVE METHOD: 1/128DUTY, 1/128BIAS
  8. CONTROLLER: ST7571
  9. BACKLIGHT TYPE: WHITE
  10. BACKLIGHT SUPPLY VOLTAGE: 3.0V



WAYING (HONGKONG) SHARES LIMITED

DESIGN:

MODEL NUMBER:

UNITS: MM

CHECK:

WYM128128K5G

VERSION: A

APPROVE:



SHEET: 1 OF 1

Unspecified tolerances are ±0.3

DATE: 2016-10-21