



CON&SEFG LAYOUT

PIN	SYMBOL	CONNECT
30	PS0	+3.0V
29	PS1	
28	CSB	P3.0
27	RST	P3.1
26	A0	P3.2
25	ENR	P3.3
24	ERD	P3.4
23	D0	P1.0
22	D1	P1.1
21	D2	P1.2
20	D3	P1.3
19	D4	P1.4
18	D5	P1.5
17	D6(SCL)	P1.6
16	D7(SL)	P1.7
15	VDD	+3.0V
14	VSS	
13	VMD	
12	NC	x
11	V0	
10	XV0	
9	VDD1	+3.0V
8	OSCI	
7	DCPS	
6	VSS1	
5	CSEL	
4	VDT	+3.0V
3	VG	
2	VPP	x
1	VE	x

- NOTES:
1. DISPLAY TYPE: FSTN
  2. POLARIZER TYPE: TRANSPARENT, POSITIVE
  3. VIEW DIRECTION: 6:00
  4. OPERATING TEMPERATURE: -20°C~+70°C
  5. STORAGE TEMPERATURE: -30°C~+80°C
  6. VDD: +3.3V
  7. DRIVE METHOD: 1/128DUTY, 1/12BIAS
  8. CONTROLLER: ST7571
  9. BACKLIGHT TYPE: WHITE
  10. BACKLIGHT SUPPLY VOLTAGE: 3.0V

<b>WAYING (HONGKONG) SHARES LIMITED</b>		DESIGN:	MODEL NUMBER:
		CHECK:	WYM128128K6G
APPROVE:		UNITS:	MM
Unspecified tolerances are ±0.3		VERSION:	A
		SHEET:	1 OF 1
		DATE:	2016-12-13