




PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14
SIGNAL	P/S	C86	V0	V1	V2	V3	V4	CAP2N	CAP2P	CAP1P	CAP1N	CAP3P	VOUT	VSS
SIGNAL	VDD	D7	D6	D5	D4	D3	D2	D1	DO	/RD	/WR	AO	/RES	/CS1



- NOTES:**
1. DISPLAY TYPE: FFSTN
  2. POLARIZER TYPE: NEGATIVE
  3. VIEW DIRECTION: 6:00
  4. OPERATING TEMPERATURE: -20°C~+70°C
  5. STORAGE TEMPERATURE: -30°C~+80°C
  6. VDD: +3.3V
  7. DRIVE METHOD: 1/49DUTY,1/8BIAS
  8. CONTROLLER: ST7565R
  9. BACKLIGHT TYPE: WHITE
  10. BACKLIGHT SUPPLY VOLTAGE:

 <b>WAYING (HONGKONG) SHARES LIMITED</b>			
DESIGN:	MODEL NUMBER:	UNITS:	MM
CHECK:	WYM12848K1G	VERSION:	A
APPROVE:		SHEET:	1 OF 1
Unspecified tolerances are ±0.3		DATE:	2013-11-19