



PIN ASSIGNMENT	Example SPI Interface
1 VDD	+3.0V
2 VDD	+3.0V
3 VSS	1)
4 VSS	1)
5 /CS	P3.0
6 A0	P3.2
7 RESET	P3.1
8 SOL	P1.6
9 SDA	P1.7
10 GND	X

- NOTES:**
1. DISPLAY TYPE: FSTN
  2. POLARIZER TYPE: TRANSPARENT, POSITIVE
  3. VIEW DIRECTION: 6:00
  4. OPERATING TEMPERATURE: -20°C~+70°C
  5. STORAGE TEMPERATURE: -30°C~+80°C
  6. VDD: +3.3V
  7. DRIVE METHOD: 1/64DUTY, 1/9BIAS
  8. CONTROLLER: ST7525
  9. BACKLIGHT TYPE: WHITE
  10. BACKLIGHT SUPPLY VOLTAGE: 3.0V

		<b>WAYING (HONGKONG) SHARES LIMITED</b>	
DESIGN:		MODEL NUMBER:	<b>WYM19264K6G</b>
CHECK:		VERSION:	<b>A</b>
APPROVE:		SHEET:	<b>1 OF 1</b>
Unspecified tolerances are ±0.3			DATE: 2018-09-29