


- 1. DISPLAY TYPE: STN-Y-G MODE
- 2. VIEWING DIRECTION: 6:00
- 3. POLARIZER MODE: TRANSPARENT/POSITIVE
- 4. IC: UC1698U-NOP-2
- 5. OPERATING TEMP: -40°C-+70°C
- 6. STORAGE TEMP: -40°C-+80°C
- 7. Drive Method: 1/128duty 1/12bls
- 8. LCD OPERATING VOLTAGE: 1.53V
- RECOMMEND VDD: 3.3V
- 9. BACKLIGHT: WITHOUT BACKLIGHT
- 10. UNMARKED TOLERANCES: ±0.3mm
- 11. REQUIREMENT ON ENVIRONMENTAL PROTECTION: Q/S0002 (RoHS requirements contained).



NO.	SYMBOL
1	VLCD
2	VS+
3	VS-
4	VB0-
5	VB1-
6	VB1+
7	VB0+
8	VDD
9	VSS
10	TEST4
11	BM1
12	BM0
13	CS1
14	CS0
15	A0
16	RD
17	WR
18	RST
19	D0
20	D1
21	D2
22	D3
23	D4
24	D5
25	D6
26	D7

CONTROL DIMENSION:		2D Rev.	3D Rev.
EE CHECKED	李凤超	2018.7.16	
ME CHECKED	石龙飞	2018.7.16	
DESIGNED	周梅	2018.7.16	
REFERENCE DIMENSION:	()		
PRODUCT NUMBER:	WVMA240128K301G		
PART NAME:			
DRAWING NUMBER:			
MATERIAL NUMBER:			
3rd ANGLE			
UNIT	mm		
SCALE	1:1		
PAGE	1/1		