



说明:  
硅胶需覆盖IC



DOTS FUNCTION TABLE:



16	BMO	16	BMO
15	BMI	15	BMI
14	TEST14	14	TEST14
13	VSS	13	VSS
12	VDD	12	VDD
11	VDD23	11	VDD23
10	VBO+	10	VBO+
9	VBI+	9	VBI+
8	VBI-	8	VBI-
7	VBO-	7	VBO-
6	VS-	6	VS-
5	VS+	5	VS+
4	VLCD/IN	4	VLCD/IN
3	VLCD/OUT	3	VLCD/OUT
2	NC	2	NC
1	NC	1	NC

CONFIRM ALL TYPE DRAWINGS OF THIS AND PASS BACK!

OPERATING VOLTAGE: 3.0V	OPERATING CURRENT: --
DISPLAY TYPE: STN-BLUE/NEGATIVE	POLARIZER MODE: TRANSMISSIVE
LCD DRIVE METHOD: 1/128DUTY 1/128IAS 16.0V	VIEW DIRECTION: 6:00 O'CLOCK
LCD DRIVER IC: UC1698U	BACK LIGHT: --
OPERATING TEMPERATURE: -20°C TO 70°C	STORAGE TEMPERATURE: -30°C TO 80°C
DEFAULT TOLERANCE: ±0.2	ROHS STANDARD: YES

<b>WAYING (HONGKONG) SHARES LIMITED</b>			
TITLE	规格外形图	CUSTOMER NUMBER	
DES'D BY	赵雅	PRODUCT MODEL	WTM240128K6G
CHK'D BY		SERIAL NUMBER	
APPROVED		SCALE	1:1
		REV	A
		UNIT	mm
		DATE	2016-06-15
		NO.	1/1