




PIN ASSIGNMENT		Example (GSP 0)	
NO.	FUNCTION	MC/VSS	MC/VSS
1	ESD		
2	SDI	P1.7	
3	SDO	P1.6	
4	RSIB	P3.2	
5	AO	P3.1	
6	GSR	P3.0	
7	VSS		
8	VDD1		
9	VDDA	+3.3V	
10	CATN		C-1UF
11	CATP		C-1UF
12	XV0		
13	V0		
14	VG		
15	ESD		MC/VSS



- NOTES:**
1. DISPLAY TYPE: FSTN
 2. POLARIZER TYPE: TRANSPARENT, POSITIVE
 3. VIEW DIRECTION: 12:00
 4. OPERATING TEMPERATURE: -20°C~+70°C
 5. STORAGE TEMPERATURE: -30°C~+80°C
 6. VDD: +3.3V
 7. DRIVE METHOD: 1/160DUTY, 1/13BIAS
 8. CONTROLLER: ST75256
 9. BACKLIGHT TYPE: WHITE
 10. BACKLIGHT SUPPLY VOLTAGE: 3.0V

WAYING (HONGKONG) SHARES LIMITED		DESIGN:	MODEL NUMBER:
		CHECK:	WYM240160K5G
APPROVE:		UNITS:	MM
		VERSION:	A
		SHEET:	1 OF 1
		DATE:	2018-12-06

Unspecified tolerances are ±0.3