



Pin No.	Symbol
1	NC
2	V <sub>PP</sub>
3	EXTB
4	D7
5	D6
6	D5
7	D4
8	D3
9	D2
10	D1
11	00
12	RSTB
13	R00R
14	ERD
15	A0
16	CSB
17	IF0
18	IF1
19	IF2
20	VSS
21	VDD
22	CATN
23	CATP
24	X00
25	V0
26	VG
27	LEDA
28	LEBK(O)
29	LEBK(W)
30	NC



LED CIRCUIT DIAGRAM

DOTS SIZE 20: 1

- NOTES:**
1. DISPLAY TYPE: FSTN
  2. POLARIZER TYPE: TRANSPARENT, POSITIVE
  3. VIEW DIRECTION: 6:00
  4. OPERATING TEMPERATURE: -20°C~+70°C
  5. STORAGE TEMPERATURE: -30°C~+80°C
  6. VDD: +3.3V
  7. DRIVE METHOD: 1/64DUTY, 1/9BIAS
  8. CONTROLLER: ST75256
  9. BACKLIGHT TYPE: WHITE
  10. BACKLIGHT SUPPLY VOLTAGE: 3.0V

		WAYING (HONGKONG) SHARES LIMITED	
DESIGN:	MODEL NUMBER:	UNITS:	MM
CHECK:	WYM256128K1G	VERSION:	A
APPROVE:		SHEET:	1 OF 1
Unspecified tolerances are ±0.3		DATE:	2020-06-14